

AquaMax

5800 SXT Water Softener

When water quality matters, AquaMax residential water softeners and filtration systems deliver. Featuring Pentair's patented Fleck technology and backed by superior after-sales support, AquaMax systems are designed with Canadian families in mind.

Enhance the quality of your water with the Fleck 5800SXT Residential Water Softener.

- Silky soft skin & hair after showering
- Clothes are brighter, softer & last longer
- Glasses & dishware are spot free
- Use 50% less detergent, fabric softeners, soap, shampoo & personal moisturizers
- Add years of life to water heaters, dishwashers & washing machines

Water treatment solutions engineered for your unique water needs.

AquaMax is a brand of **Interpump**

Water specialists delivering pump and water treatment solutions since 1982.

interpump.ca



Fleck 5800SXT

Residential Water Softener

FEATURES

- 5-cycle programming
- Fast-positioning, reversible 10,000 RPM 12-volt DC drive motor
- Seal and spacer cartridge for easy servicing
- LCD backlit display for low-light conditions
- Precision cycle positioning
- Soft water refill for better brine saturation and cleaner brine tank
- Programming memory backup in case of power low/outages

System includes: Control valve featuring SXT electronic timer, 3/4" paddle water meter, 3/4" MPT poly bypass assembly and Pentair poly glass media vessel with 1" ABS internal distribution.

Softener includes: High quality Structural mineral and brine tanks. Brine tank c/w salt shelf and Fleck 2310 brine safety float assembly. Uses high purity, fine mesh, premium grade cation exchange resin.



Specifications

Model Number	Resin (CuFt)	Tank Sizes		Unit Cap		Flow Rates		BKW (GPM)	Salt		Weight (lbs)
		Resin Tank	Brine Tank	Min	Max	Service	Peak		10	15	
24K58SXT	0.75	8" x 44"	14" x 34"	18K	24K	4	8	1.5	8	12	85
30K58SXT	1.0	9" x 48"	14" x 34"	24K	30K	5	10	2.0	10	15	95
40K58SXT	1.3	10" x 47"	14" x 34"	32K	40K	5.5	11	2.4	13	20	125
60K58SXT	2	12" x 52"	18" x 40"	48K	60K	6.5	13	3.5	20	30	170
90K58SXT	3	14" x 65"	18" x 40"	72K	90K	6.5	13	4.0	30	60	225

Capacities are based on resin manufacturer's data • Units are set to the factory minimum salt setting • Use minimum capacity when sizing • Flow rates are in U.S. Gallons/minute • Sizes and space requirements are in inches