

AquaMax

5812SXT Water Softener

When water quality matters, AquaMax residential water softeners and filtration systems deliver. Featuring Pentair's patented Fleck technology and backed by superior after-sales support, AquaMax systems are designed with Canadian families in mind.

Enhance the quality of your water with the Fleck 5812SXT Residential Water Softener.

- Silky soft skin & hair after showering
- Clothes are brighter, softer & last longer
- Glasses & dishware are spot free
- Use 50% less detergent, fabric softeners, soap, shampoo & personal moisturizers
- Add years of life to water heaters, dishwashers & washing machines

Water treatment solutions engineered for your unique water needs.

AquaMax is a brand of **Interpump**

Water specialists delivering pump and water treatment solutions since 1982.

interpump.ca



PENTAIR
FLECK®



Fleck 5812SXT 1 1/4" High Performance Residential Water Softener

FEATURES

- 3 or 5-cycle programming
- Fast-positioning, reversible 10,000 RPM 12-volt DC drive motor
- Seal and spacer cartridge for easy servicing
- LCD backlit display for low-light conditions
- Precision cycle positioning
- Soft water refill for better brine saturation and cleaner brine tank
- Programming memory backup in case of power low/outages

System includes: Control valve featuring SXT electronic timer, 1 1/4" turbine water meter, 1 1/4" bypass, 1" MPT poly bypass adapters and Structural poly glass media vessel with 1" ABS internal distribution.

Softener includes: High quality Structural mineral and brine tanks. Brine tank c/w salt shelf and Fleck 2310 brine safety float assembly. Uses high purity, premium grade cation exchange resin.



Specifications

Model Number	Resin (CuFt)	Tank Sizes		Unit Cap		Flow Rates		BKW (GPM)	Salt		Weight (lbs)
		Resin Tank	Brine Tank	Min	Max	Servi	Peak		10	15	
45K52SXT	1.5	10" x 54"	14" x 34"	40K	45K	6	7.5	2.4	15	23	138
60K52SXT	2.0	12" x 52"	14" x 34"	52K	60K	8	10	3.5	20	30	195
75K52SXT	2.5	13" x 54"	14" x 34"	65K	75K	10	12.5	4.0	25	38	225
90K52SXT	3	14" x 65"	18" x 40"	78K	90K	12	15	5.0	30	45	240
120K52SXT	4	16" x 65"	24" x 48"	104K	120K	16	20	7.0	40	60	395

Capacities are based on resin manufacturer's data • Units are set to the factory minimum salt setting • Use minimum capacity when sizing • Flow rates are in U.S. Gallons/minute • Sizes and space requirements are in inches