

# AquaMax

## Performa 762/268 Water Softener

When water quality matters, AquaMax residential water softeners and filtration systems deliver. Featuring Pentair's patented Autotrol technology and backed by superior after-sales support, AquaMax systems are designed with Canadian families in mind.

Enhance the quality of your water with the Autotrol Performa 762/268 Electronic Control Residential Water Softener.

- Silky soft skin & hair after showering
- Clothes are brighter, softer & last longer
- Glasses & dishware are spot free
- Use 50% less detergent, fabric softeners, soap, shampoo & personal moisturizers
- Add years of life to water heaters, dishwashers & washing machines

**Water treatment solutions engineered  
for your unique water needs.**

AquaMax is a brand of **Interpump**

Water specialists delivering pump and water treatment solutions since 1982.

[interpump.ca](http://interpump.ca)



# Autotrol Performa 762/268 Residential Water Softener

## FEATURES

- DuraFlow valve disk operation which seats vertical to provide frictionless sealing
- Fully adjustable 5 or 8 cycle control
- Designed with double backwash for reduced hardness leakage
- Optical sensor for precision cycle positioning
- Soft water refill for better brine saturation and cleaner brine tank
- Programming memory backup in case of power low/outages

**System includes:** Control valve featuring 762 professional level electronic timer, 3/4" water meter, poly bypass w/ 3/4" copper tail-kit assembly and Pentair poly glass media vessel with 1" ABS internal distribution.

**Softener includes:** High quality structural mineral tank, 28-gallon brine tank with salt shelf & brine safety float assembly. Uses high purity premium grade cation exchange resin.



## Specifications

Model Number	Resin (CuFt)	Tank Sizes		Unit Cap		Flow Rates		BKW (GPM)	Salt		Weight (lbs)
		Resin Tank	Brine Tank	Min	Max	Service	Peak		10	15	
24KPLM	0.75	8" x 44"	14" x 34"	18K	24K	4	8	1.5	8	12	85
30KPLM	1.0	9" x 48"	14" x 34"	24K	30K	5	10	2.0	10	15	95
40KPLM	1.3	10" x 47"	14" x 34"	32K	40K	5.5	11	2.4	13	20	125
60KPLM	2	12" x 52"	18" x 40"	48K	60K	6.5	13	3.5	20	30	170
90KPLM	3	14" x 65"	18" x 40"	72K	90K	6.5	13	4.0	30	60	225

Capacities are based on resin manufacturer's data • Units are set to the factory minimum salt setting • Use minimum capacity when sizing • Flow rates are in U.S. Gallons/minute • Sizes and space requirements are in inches